



THANK YOU FOR PURCHASING A CUSTOM EXHAUST FOR YOUR HONDA RUCKUS.

TO INSTALL YOUR EXHAUST PLEASE USE THESE FOLLOWING STEPS.

1. INSTALL THE MUFFLER BRACKET TO THE BACK OF THE MOTOR (BEHIND THE RADIATOR)USING THE 50MM LONG BOLTS , AT THIS POINT LEAVE THE BRACKETS LOOSE, BUT ALIGNED WITH BOLTS FINGER TIGHT
2. NEXT, INSTALL YOUR EXISTING MUFFLER GASKET UNDER THE HEAD OF THE MOTOR FOLLOWED BY THE FLANNGE PORTION OF THE HEADER. ADDITIONALLY LEAVE THE HEADER ONLY FINGER TIGHT AT THIS POINT.
3. PUT THE RUBBER AROUND BAND (THIS IS TIME CONSUMING) WRAP BAND AROUND MUFFLER
4. ALIGN THE FINAL BOLT THROUGH THE MUFFLER BAND. AND INTO THE BRACKET INSTALLED IN STEP 1.
5. SLOWLY TIGHTEN ALL THE REMAINING BOLTS LITTLE AT A TIME EACH BOLT SO THE SYSTEM COMES TO REST IN THE DESIRED POSTION.